



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

NATIONAL TECHNICAL SYSTEMS CANADA INC.
2425 Industrial Blvd.
Chambly, Québec, J3L 4W3, Canada
Jean-Pierre Rioux Phone: 514 651 6312
E-mail: jean-pierre.rioux@nts.com

MECHANICAL

Valid To: September 30, 2020

Certificate Number: 0214.49

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following tests on Aerospace, Railway, Automotive, Photonic, Consumer, Medical and Material products:

<u>Test:</u>	<u>Test Method(s):</u>
Vibration	MIL-STD-883 Method 2005 TC: A, B, Method 2007 TC: A, Method 2026 TC: A to F;
	MIL-STD-810 Method 514;
	MIL-STD-202 Method 201, Method 204 TC: A, B, C, D, F, G, Method 214 TC: A to F;
	IEC 60068-2-6;
	IEC 60068-2-64;
	IEC 60255-21-1;
	IEC 61373;
	RTCA/DO-160;
	JEDEC JESD22-B103;
	GMW 3172 Section 9.3.1, Section 9.3.2, Section 10.2;
	GMW 15310 Section 4.3.8;

Test:

Test Method(s):

Vibration (*cont.*)

GMW 16288 Section 3.2.1.2.3;
Chrysler CS-11982 Section 4.2.3;
Chrysler CS-00056 Section 5.4.3;
Chrysler PF-12184 Section 3.1;
Chrysler PF-90135 Section 9.6;
ISO 16750-3 Section 4.1;
SAE J1455;
ANSI C136.31;
Telcordia GR-1221;
CSA C22.2 No.137 Vibration only;
CSA C22.2 60601-1-11;
CSA C22.2 60601-1-12;
UL 844 Vibration only;
NEMA TS 2 Section 2.2.8

Mechanical Shock

MIL-STD-883 Method 2002 TC: A, B;
MIL-STD-810 Section 516;
MIL-STD-202 Section 213 TC: A to K;
IEC 60068-2-27;
IEC 60255-21-2;
IEC 61373;
RTCA/DO-160;
JEDEC JESD22-B104 A to H;
GMW 3172 Section 9.3.3,
 Section 9.3.4,
 Section 9.3.5;



Test:

Test Method(s):

Mechanical Shock (cont.)

Chrysler CS-11982 Section 4.2.4,
Section 4.2.5;

Chrysler CS-00056 Section 5.4.4, 5.4.5;

ISO 16750-3 Section 4.2;

SAE J1455;

Telcordia GR-1221;

CSA C22.2 60601-1-11;

CSA C22.2 60601-1-12;

NEMA TS 2 Section 2.2.9

Temperature Steady State

MIL-STD-810 Method 501,
Method 502;

IEC 60068-2-1;

IEC 60068-2-2;

RTCA/DO-160;

JEDEC JESD22-A101,
JESD22-A103,
JESD22-A119;

GMW 3172 Section 9.4.1;

GMW 15310 Section 4.3.4;

GMW 15725 Section 4.4,
Section 4.5;

GMW 16288 Section 3.2.1.1.3,
Section 3.2.1.1.4;

Chrysler CS-11982 Section 4.1.1,
Section 4.1.2;

Chrysler CS-00056 Section 5.3.1, 5.3.2;

Chrysler PF-12184 Section 3.4,
Section 3.5;



<u>Test:</u>	<u>Test Method(s):</u>	
Temperature Steady State (cont.)	ISO 16750-4	Section 5.1;
	SAE J1455;	
	Telcordia GR-1221	Section 6.2.4, Section 6.2.6;
	CSA C22.2 60601-1-11;	
	CSA C22.2 60601-1-12;	
	NEMA TS 2	Section 2.2.7 Test C, D, E, F, G
Temperature Variation	MIL-STD-883	Method 1010;
	MIL-STD-810	Method 503;
	MIL-STD-202	Method 107;
	IEC 60068-2-14	Tests Na, Nb;
	RTCA/DO-160;	
	JEDEC	JESD22-A104, JESD22-A105;
	GMW 3172	Section 9.4.2, Section 9.4.3;
	GM 6139M ¹	Section 3.9;
	Chrysler PF-12032	Section 7.5;
	Chrysler PF-12184	Section 3.3;
	Chrysler PF-90135	Section 9.5;
	ISO 16750-4	Section 5.3;
	SAE J1455;	
	Telcordia GR-1221	Section 6.2.3, Section 6.2.7;
	CSA C22.2 60601-1-11;	
	CSA C22.2 60601-1-12	



Test:

Test Method(s):

Humidity

MIL-STD-810 Method 507;
MIL-STD-202 Method 103;
IEC 60068-2-3;
IEC 60068-2-30;
IEC 60068-2-38;
IEC 60068-2-56;
IEC 60068-2-78;
SAE J1455;
RTCA/DO-160;
Telcordia GR-1221 Section 6.2.5,
Section 6.2.8;
GMW 3172 Section 9.4.5,
Section 9.4.6;
GMW 15725 Section 4.3;
GM 6139M¹ Section 3.1;
Chrysler CS-11982 Section 4.1.6,
Section 4.1.7;
Chrysler CS-00056 Section 5.3.6, 5.3.7;
Chrysler PF-12184 Section 3.6;
ISO 16750-4 Section 5.6,
Section 5.7;
CSA C22.2 60601-1-11;
CSA C22.2 60601-1-12

Salt Fog / Salt Spray

MIL-STD-883 Method 1009;
MIL-STD-810 Method 509;
MIL-STD-202 Method 101;



<u>Test:</u>	<u>Test Method(s):</u>	
Salt Fog / Salt Spray (Cont.)	IEC 60068-2-11;	
	IEC 60068-2-52;	
	RTCA/DO-160;	
	GMW 3172	Section 9.4.7;
	ISO 16750-4	Section 5.5;
	ISO 9227 (NSS)	Section 5.2;
	SAE J1455;	
	ASTM B117	
Degrees of Protection Provided by Enclosures	IEC 60529	IPX1 to IPX8, IP1X to IP6X;
	ISO 20653	IPX1 to IPX8, IP1X to IP6X, IPx4K
	DIN 40 050	IPX1 to IPX8, IP1X to IP6X, IPx4K
Drop / Free Fall	IEC 60068-2-31;	
	GMW 15310	Section 4.3.7;
	GMW 16288	Section 3.2.1.1.7;
	Chrysler CS-11982	Section 4.2.6 ;
	Chrysler PF-11710	Section 4.2;
	ISO 16750-3	Section 4.3
Impact	IEC 60068-2-75	Test Ehb (Spring Hammer), Test Ehc (Vertical);
	GMW 15725	Section 4.6;
	Chrysler PF-11710	Section 4.3



<u>Test:</u>	<u>Test Method(s):</u>	
Fluid Compatibility / Resistance	RTCA/DO-160	Hydraulic Fluids / Lubricating Oils De-Icing Fluid / Fire Extinguishants, Fuels, Insecticides;
	GMW 15725	Section 4.7;
	GM 6139M ¹	Section 5.1;
	Chrysler PF-11710	Section 3.2
Vacuum / Altitude / Overpressure / Rapid Decompression	RTCA/DO-160;	
	GMW 16288	Section 3.2.1.1.8;
	Chrysler PF-12032	Section 5.2;
	SAE J1455;	
	CSA C22.2 60601-1-11;	
	CSA C22.2 60601-1-12	
Air & Fluid Pressure / Creep	RTCA/DO-160;	
	GMW 15310	Section 4.3.1, Section 4.3.5, Section 4.3.6, Section 4.3.9;
	GMW 16288	Section 3.2.1.1.2, Section 3.2.1.1.6, Section 3.2.1.2.1, Section 3.2.1.2.2;
	Chrysler PF-12032	Section 5.3, Section 5.4, Section 7.3, Section 7.4;
	Chrysler PF-12184	Section 4.3.1, Section 4.3.2, Section 4.3.3;
	Chrysler PF-90135	Section 7.1, Section 7.3, Section 9.3, Section 9.4 (limited capability)



<u>Test:</u>	<u>Test Method(s):</u>	
Boil Over	Chrysler PF-90135	Section 7.4
Cover Retention	Chrysler PF-11710	Sections 5.3, 5.4, 5.5
Wear Resistance	GM 6139M ¹	Section 3.12
Water Immersion	GM 6139M ¹	Section 3.2
Over Flow Tube Pull Off	Chrysler PF-12032	Section 5.6;
	Chrysler PF-90135	Section 7.5
Cap Effort	Chrysler PF-12184	Section 4.3.4
Cap Removal and Install Torque	GMW 15310	Section 4.3.2 ;
	Chrysler PF-90135	Section 6.1.2
Grommet Retainer Side Loading	Chrysler PF-11710	Section 5.1
Multiple Cover Removal	Chrysler PF-11710	Section 5.6
Cover Installation	Chrysler PF-11710	Section 5.7
Neutral Salt Spray & Air Blow Off	GM 6139M ¹	Section 3.3
Tape Adhesion	GM 6139M ¹	Section 3.10;
	ASTM D3359	
Coating Evaluation	ISO 4628-2;	
	ISO 4628-8;	
	ISO 4628-10	
Performance verification	GMW 3172	Section 6.1, Section 6.2, Section 6.3, Section 6.4;
Insulation Test	EN 50155 IEC 60571	Section 12.2.9; Section 12.2.10

¹Note: This Laboratory's Scope contains withdrawn, inactive or superseded methods. As a clarifier, this indicates the that applicable method itself has been withdrawn or is now considered "historical" and not that the laboratory's accreditation for the method has been withdrawn.





Accredited Laboratory

A2LA has accredited

NATIONAL TECHNICAL SYSTEMS CANADA INC.

Chambly, Canada

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 30th day of October 2018.

A handwritten signature in black ink, written over a horizontal line.

President and CEO
For the Accreditation Council
Certificate Number 0214.49
Valid to September 30, 2020

For the tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.